



MATERIAL SAFETY DATA SHEET

This Material Safety Data Sheet complies with the Canadian Controlled Products Act

****NOTE: THE FOLLOWING INFORMATION PROVIDED IS FOR THE PRODUCT CONCENTRATE ONLY, NOT FOR USE-DILUTIONS****

SECTION 1 – PRODUCT IDENTIFICATION					
PRODUCT IDENTIFIER:		BUNKER BREAKER II			
PRODUCT USE:		DEMULSIFIER FOR BUNKER/ LUBE OIL WASTE TREATMENT			
SUPPLIER:		Velocity Chemicals Ltd. Unit #1, 9515- 190 th St., Surrey, B.C. V4N-3S1 Emergency Telephone: (604) 881-4700 Facsimile: (604) 881-4701		In case of transporation emergency or product spill, contact: In Canada- CANUTEC @ 613-996-6666 (24 hrs.)	
SECTION 2 – HAZARDOUS INGREDIENTS					
HAZARDOUS INGREDIENTS	% (W/W)	CAS NUMBER	LD50	LC50	EXPOSURE LIMITS
Kerosene	40-70	8008-20-6	>5 g/kg (oral, rat) > 2g/kg (skin, rabbit)	>2.5 g/m3 (inhal., 4hrs, rat)	ACGIH= 200mg/m3 (TLV-TWA)
Alkyl Benzenesulfonic Acid	15-40	68584-22-5	Not available	Not available	Not established
SECTION 3 – PHYSICAL DATA					

<p>Physical state: liquid</p> <p>Solubility: dispersible in water</p> <p>Odour and Appearance: clear, dull dark grey with petroleum odor</p> <p>pH (100%) @ 20°C: < 2.0</p> <p>Specific Gravity @ 20°C: 0.92</p> <p>Odour Threshold (ppm): not established</p>	<p>Vapour Density: not determined</p> <p>Vapour Pressure: not determined</p> <p>Evaporation Rate: not determined</p> <p>Boiling Point (°C): not determined</p> <p>Freezing Point (°C): not determined</p> <p>Coefficient of water/oil distribution: not determined</p>
---	--

BUNKER BREAKER II

SECTION 4 – FIRE AND EXPLOSION DATA

<p>Flammability: Yes, combustible under WHMIS B3</p> <p>If yes, under what condition: heat, open flames, sparks and other ignition sources</p> <p>Means of Extinction: Dry chemical, alcohol foam, CO₂, water spray. Use extinguishing media suitable for surrounding fires.</p> <p>Special Fire Fighting Procedures: Wear NIOSH/OSHA approved, self contained breathing apparatus for fire fighting situations. Use water spray to cool all nearby fire exposed surfaces.</p> <p>Explosion Data-</p> <p>Sensitivity to impact: None</p> <p>Sensitivity to static discharge: None</p>	<p>Flash Point (°C) and method: 41°C (PMCC)</p> <p>Upper Flammable limit (% volume): not applicable</p> <p>Lower Flammable limit (% volume): not applicable</p> <p>Autoignition temperature (°C): not applicable</p> <p>Hazardous combustion products: carbon oxides, sulfur oxides, toxic sulfuric acid vapors and other toxic organic vapours.</p>
---	---

SECTION 5 – REACTIVITY DATA

<p>Chemical Stability: yes, stable under normal storage conditions</p> <p>If no, under what conditions:</p> <p>Incompatibility with other substances: yes</p> <p>If so, under what conditions: strong acids, alkalis and oxidizers</p> <p>Reactivity, and under what conditions: none known</p> <p>Hazardous Decomposition Products: carbon oxides, sulfur oxides and toxic sulfuric acid vapors upon thermal decomposition.</p>
--

SECTION 6 – TOXICOLOGICAL PROPERTIES

Primary route of entry: skin and eye contact, inhalation

Effects of Acute Exposure to Product: Product exposure may cause irritation or burns to skin and eyes. Inhaling mist or vapors may cause immediate irritation to mucous membrane, discomfort to respiratory system and central nervous system(CNS) effects. Symptoms may include headaches, loss of coordination, nausea, etc.

Effects of Chronic Exposure to Product: Prolonged exposure may cause skin dermatitis.

Exposure Limits: see Section 2 under Hazardous Ingredients

Irritancy of Product: may be corrosive to skin, eyes and respiratory system.

Sensitization: none known

Reproductive Toxicity: none known

Mutagenicity: none known

Carcinogenicity: none known

Teratogenicity: none known

Synergistic Products: none known

BUNKER BREAKER II

SECTION 7 – PREVENTATIVE MEASURES

Respiratory Protection: Use a NIOSH/OSHA approved for acid mist/dust and organic vapor respirator.

Gloves: nitrile, neoprene or viton

Eye Protection: splash proof chemical goggles or face shield.

Footwear: boots

Clothing: long sleeve coveralls

Other: neoprene apron

Engineering Controls: General ventilation for normal operating conditions or local exhaust for confined areas.

Leak and Spill Procedures: Wear protective equipment. Extinguish all nearby ignition sources. Contain spill. Prevent runoff to drains or sewers. Recover material by vacuum or pump into a suitable flammable waste container. Soak up residue with suitable absorbent, and then dispose of into a flammable waste container. Reuse material if possible, or otherwise neutralize with soda ash before disposal. Dispose in accordance with local regulations.

Waste Disposal: Dispose of in accordance with local environmental regulations.

Handling Procedures and Equipment: Use good hygiene practices. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use with adequate ventilation. Use proper grounding procedures when handling. Empty container may contain flammable residues/vapors. Do not cut, puncture, or weld near empty container. Safety Shower and Eye wash station should be available in the immediate work area.

Storage Requirements: Store in a cool, dry place away from all nearby ignition sources and incompatibles. Do not mix with any other chemicals. Keep container closed when not in use. Keep storage temperature between 4°C to 30°C.

Special Shipping Information:

WHMIS Classification: B3, E

TDG Classification:

Flammable Liquid, Corrosive, N.O.S. (Kerosne & AlkylBenzenesulfonic Acid Mixture), Class 3(8), UN 2924, P.G. III

SECTION 8 – FIRST AID MEASURES

Inhalation: Remove victim to fresh air, apply artificial respiration if necessary. Seek medical help.
Ingestion: Give large amounts of water if conscious. Do not induce vomiting. Get medical help immediately.
Skin Contact: Wash thoroughly with water for 15 minutes. If irritation persist, seek medical attention.
Eye Contact: Flush immediately with water for 15-20 minutes. Seek medical help.

SECTION 9 - OTHER INFORMATION

REVISIONS: September 7, 2010

SUPERCEDES: August 10, 2010

PREPARED BY: Technical Department (Customer Service phone number: 604-881-4700)

DISCLAIMER: The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Velocity Chemicals Ltd. expressly disclaims all expressed or implied warranties and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.