

MATERIAL SAFETY DATA SHEET

This Material Safety Data Sheet complies with the Canadian Controlled Products Act

NOTE: THE FOLLOWING INFORMATION PROVIDED IS FOR THE PRODUCT CONCENTRATE ONLY, NOT FOR USE-DILUTIONS

SECTION 1 – PRODUCT IDENTIFICATION									
PRODUCT IDENTIFIER:	PAC-D								
PRODUCT USE:	Coagulant additive for wastewater treatment								
SUPPLIER: Velocity Chemicals Ltd. Unit #1, 9515- 190 th St., Surrey, B.C. V4N-3S1 Emergency Telephone: (604) 881-4700 Facsimile: (604) 881-4701						In case of transporation emergency or product spill, contact: In Canada- CANUTEC @ 613-996-6666 (24 hrs.)			
	S	ECTION 2	– HAZARDOU	S ING	REDIENTS	6			
HAZARDOUS INGREDIENTS	% (W/W)	CAS NUMBER	LD50	LC50		EXPOSURE LIMITS			
Polyhydroxy Aluminum Chloride	15-40	1347-41-9	Not available	N	lot available	OSHA(PEL) & ACGIH (TLV)= 2 mg/m3 (as Al)			
SECTION 3 – PHYSICAL DATA									

Physical state: liquid	Vapour Density: not determined					
Solubility: soluble	Vapour Pressure@ 20°C: not determined					
Odour and Appearance: clear and odorless	Evaporation Rate: not determined					
pH (100%) @ 20°C: 2.2-2.8	Boiling Point (°C): not determined					
Specific Gravity @ 20°C: 1.17-1.18	Freezing Point (°C): not determined					
Odour Threshold (ppm): not determined	Coefficient of water/oil distribution: Greater than 1					
PAC-D						
SECTION 4 – FIRE AND	EXPLOSION DATA					
Flammability: No, product is non-flammable.	Flash Point (°C) and method: not applicable					
If yes, under what condition: Not applicable.	Upper Flammable limit (% volume): not applicable					
Means of Extinction : Dry chemical, alcohol foam, CO ₂ ,	Lower Flammable limit (% volume): not applicable					
water spray. The product is not flammable. Use extinguishing media suitable for surrounding fires.	Autoignition temperature (°C): not applicable					
Special Fire Fighting Procedures: Wear NIOSH/OSHA approved, self contained breathing apparatus for fire fighting situations. Use water spray to cool all nearby fire exposed surfaces. Explosion Data-	Hazardous combustion products: will liberate toxic, corrosive fumes of hydrogen chloride and carbon oxides.					
Sensitivity to impact: None						
Sensitivity to static discharge: None						
SECTION 5 – REACTIVITY DATA						
Chemical Stability: yes, stable under normal storage conditions						
If no, under what conditions:						
Incompatibility with other substances: yes						
If so, under what conditions: strong alkalis, strong oxidizers and reducing agents, organic materials, and sensitive metals like aluminum and its alloys.						
Reactivity, and under what conditions: none known						
Hazardous Decomposition Products: will liberate toxic, corrosive fumes of hydrogen chloride and carbon oxides.						

SECTION 6 – TOXICOLOGICAL PROPERTIES

Primary route of entry: skin and eye contact, and inhalation

Effects of Acute Exposure to Product: Product exposure may cause skin and eye irritation or burns. Inhaling mist or vapors can cause immediate irritation, burns or discomfort to respiratory system.

Effects of Chronic Exposure to Product:: no known chronic health effects

Exposure Limits: see Section 2 under Hazardous Ingredients Irritancy of Product: corrosive to skin, eyes and respiratory system. Sensitization: none known Reproductive Toxicity: none known	Mutagenicity: none known Carcinogenicity: none known Teratogenicity: none known Synergistic Products: none known
---	---

PAC-D

SECTION 7 – PREVENTATIVE MEASURES Respiratory Protection: Normally not required. Use a NIOSH/OSHA approved for acid mist/dust respirator if mists or vapors are present. Footwear: rubber boots Gloves: butyl, rubber, neoprene or viton Clothing: long sleeve coveralls and rubber apron Other: Eye Protection: splash proof chemical goggles or face shield Footwear: value of the state of the st

Engineering Controls: General ventilation for normal operating conditions or local exhaust for confined areas.

Leak and Spill Procedures: Wear protective equipment. Contain spill. Prevent runoff to drains or sewers. Recover material by pumping into a suitable waste container. Reuse material if possible, or otherwise neutralize with soda ash before disposal. Dispose in accordance with local regulations.

Waste Disposal: Dispose of in accordance with local environmental regulations.

Handling Procedures and Equipment: Use good hygiene practices. Avoid contact on skin, eyes or clothing. Avoid inhaling mists or vapors. Safety shower and eye wash station should be available in the immediate work area.

Storage Requirements: Store in a cool, dry place away from incompatibles. Do not mix with any other chemicals. Keep container closed when not in use. Keep from freezing and temperatures below 30°C.

Special Shipping Information:

WHMIS Classification: E

TDG Classification:

Corrosive Liquid, Acidic, Inorganic, N.O.S. (Polyhydroxy Aluminum Chloride Mixture), Class 8, UN3264, P.G.III

SECTION 8 – FIRST AID MEASURES

Inhalation:
Ingestion:Remove victim to fresh air, apply artificial respiration if necessary. Seek medical help.Skin Contact:
Eye Contact:Remove victim to fresh air, apply artificial respiration if necessary. Seek medical help.Give large amounts of water if conscious. Do not induce vomiting. Get medical help immediately.
Wash thoroughly with water for 15 minutes. If irritation persist, seek medical attention.
Flush immediately with water for 15-20 minutes. Seek medical help.

SECTION 9 - OTHER INFORMATION								
REVISIONS:	October 26, 2012	SUPERCEDES:	October 15, 2010					
PREPARED BY:	Technical Department (Customer Service phone number: 604-881-4700)							
DISCLAIMER:	The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Velocity Chemicals Ltd. expressly disclaims all expressed or implied warranties and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.							